



| WORKSTATIONS | |
|--|---|
| Processor | Intel P4 (2.6 GHz), Intel Dual-Core (1.6GHz) or higher configuration |
| Memory | 1GB eCW + MSOffice 2003 – 2007 2GB eCW + MS Office 2003 – 2007 + Dragon Medical V. 10 |
| Hard Drive | 10 GB of free space |
| Operation System | Windows XP Pro SP3 / VISTA Business (32-Bit), Enterprise (32-Bit), Ultimate (32-Bit), Windows 7 Enterprise (32-Bit), Ultimate (32-Bit), Professional (32-Bit) |
| NOTE: Billing computers may require a separate modem and separate dedicated analog phone line based on your clearing house OR direct claim submissions to payers. No VOIP or DSL lines. No splitter or filter. | |

| TABLETS/LAPTOPS | |
|------------------|--|
| Processor | Intel Pentium M with Centrino Mobile Tech 1.0 GHz |
| Memory | 1GB eCW + MS Office 2003-2007 2GB eCW + MS Office 2003-2007 + Dragon Medical V. 10 |
| Hard Drive | 10 GB of free space |
| Operation System | Windows XP Tablet Edition 2005 SP3/Windows XP Pro SP3 / VISTA Business (32-Bit), Enterprise (32-Bit), Ultimate (32-Bit), Windows 7 Enterprise (32-Bit), Ultimate (32-Bit), Professional (32-Bit) |
| Network | 802.11 G or N Wireless |

| PERIPHERALS | |
|--------------|---|
| Printers | Laser Printer must support PCL5 or higher (All-in-one devices CANNOT be used as a scanner but can be used as printing devices ONLY) |
| Scanner | Twain v1.2 Compatible drivers required. <i>Recommended Model(s)</i> : Fujitsu fi-6130C or fi-6230C, Panasonic KVS10xxx |
| Router | Secure encrypted connectivity for communication between facilities is required --- Recommended models: Linksys RV042, Linksys RV082, SonicWALL TZ190, SonicWALL TZ210, Cisco ASA 5505 |
| Access Point | 802.11G Compatible or higher. <i>Recommended Model(s)</i> : Cisco Aironet, SonicWALL TZ190 |
| Card Scanner | MedicScan OCR supported. (OCR works for some Driver's license not for insurance cards) Please check website for details http://store.card-reader.com/t-eclinicalworks.aspx |

| FAX SERVER REQUIREMENTS | | | | | | |
|--|----------------|---|--------|-----|------|--|
| Analog Fax 1 Port | 1 ¹ | 1 | 2.6GHz | 1GB | 10GB | Microsoft Windows XP Pro SP3 (32-Bit only) |
| Analog fax requirements (above) are only applicable to standard 1 Port Mainpine IQ Express --- PCI-E slot required | | | | | | |

| | | | | | | |
|--|----------------|---|--------|-----|------|--|
| Analog Fax 2 / 4 Port | 1 ¹ | 1 | 2.6GHz | 4GB | 10GB | Microsoft Windows 2003 – 2008 32 / 64-Bit (Standard / Enterprise) |
| ¹ Analog fax requirements (above) are only applicable to standard 2 / 4 Port Mainpine IQ Express --- PCI-E slot required | | | | | | |
| Fax servers require a separate modem and separate dedicated analog or digital phone line based on the solution type. No VOIP or DSL lines. No splitter or filter. Analog fax server software is not supported on any version of Windows VISTA. | | | | | | |

| | |
|-------------|-----------------------------------|
| Digital Fax | eCW to host digital fax solution. |
|-------------|-----------------------------------|

| CONNECTIVITY | |
|--|--|
| Alternative Connectivity Methods | VPN (B2B):SonicWALL TZ Series, Cisco ASA , Netscreen firewalls, Linksys RV series or any business class 3DES compatible device capable of creating site-to-site hardware VPN tunnels SSL Client: eClinicalWorks web-based Secure encrypted client Remote Desktop (RDC) - used for remote anywhere access outside of the office. |
| Redundant Internet Access | All practices are required to have redundant ISP internet access or sign waiver acknowledging risks involved in single point of failure on internet connection to the data centers. |
| Minimum network performance requirements | eClinicalWorks evaluates minimum network requirements based on the following parameters: Latency: Minimum 50MS latency round trip on a standard ping packet Packet Loss: Less than 1% packet loss Bandwidth: Bandwidth requirements will vary on number of users per location. Please contact your sales coordinator for details. |